




- Space-saving and reliable complete system for position, speed and length
- Up to 0.008 mm/pulse for excellent measurement results
- Suitable for any surface
- Quickly mounted and adjusted



Industrie ROBUST







Positions, speeds, travel lengths ... measure reliably and precisely

For over 25 years, Wachendorff Automation has developed and manufactured systems and rotary encoders for worldwide use in the areas of mechanical and plant construction, lift construction, mobile machinery and renewable energies.


More than 1,500 realised customer variants demonstrate our flexibility and absolute focus on the customer's needs. Owing to the high mechanical and electrical stability of our rotary encoders and systems, we provide a five-year warranty - which is unique in the world!

We support you right from the construction phase. Our strength lies in precisely matched lengths and position measuring systems for your measurement task.

With these systems, the positions, speeds and travel lengths of conveyor belts, film/paper webs or cardboard packaging, for example, can be recorded safely and efficiently.

We meet the highest requirements in an ideal way with the LMSMA2x/3x measuring systems:

- · Constant and accurate measurement results through optimal, low-slip measurement in the most varied conditions arising
 - Adjustable pressure
 - · Coordinated measuring wheels for every surface
 - Selectable resolutions from 1.0 to 0.008 mm/pulse.
- Small space requirement thanks to its compact design.
- Long service lifetimes thanks to the high mechanical robustness of all the components.
- Fast and flexible mounting on the machine.











Experience is in the detail ... save time with a system

We have significantly optimised the adjustment possibilities of the whole system, which is based on a spring arm with a central spring. This gives you constructive and valuable benefits:

Now 36 alignment positions

The newly developed hand wheel with its 10° resolution levels allows for 36 alignment positions.

In combination with the elongated holes of the angle bracket, you get much more room for the installation.

Easily adjustable preload

With the new systems, the spring preload is adjustable in steps from $5\ N$ to a maximum of $30\ N$ preload.

Calibration without disassembly

The preassembled systems for installation in the machine or readjustment during commissioning remain mounted.

Fixation in resting position

During machine setup or maintenance in particular, it is possible that the length measuring system is not designed to run. The LMSMA systems offer the possibility to fix the spring arm in a resting position. The spring arm is then returned to the working position and continues to work at the previously set pressure.

You will see that there are a number of good reasons for using the LMSMA length measuring systems.





www.wachendorff-automation.com/lms








Quickly mounted - directly on the machine ... the LMSMA2x length measuring system


To assemble, simply loosen the base plate from the hand wheel and attach it to the machine at the position defined by you. The dimensions of the holes in the blue base plate are adapted to the current attachment profiles on the market. The captive central screw enables the measuring system to connect to the base plate. Now simply adjust the preload and tighten the central screw. Job done!

Special spring for durable uniform spring force



Incremental Encoder WDGI58, extremely robust due to high bearing loads

> Base plate with adjustable resolution and holes, matched for profile rail mounting or directly on the machine




Measuring wheels with different surfaces for ideal adaptation to the measuring surface

Captive central screw for fast installation and setup

Locking pin to determine the resting position during setup or maintenance



LMSMA22 length measuring system (measuring wheel U = 200 mm / without angle bracket)



www.wachendorff-automation.com/lmsma22

LMSMA25 length measuring system (measuring wheel U = 500 mm / without angle bracket)

8		/3	MSWA	Store	o Zak	NO OCO OCO OCO OCO OCO OCO OCO OCO OCO O	No Standard	DOSTO DOSTO	No N	Story Control of the story of t	o and a series of the series o	os de la companya de	2 AND LONG	SO S	2 AMENT	South State of the	TO ACTOR ACT	OS AND OS	244	NO CONTRACTOR	2 AMENA	Story Story	10 AX	NA STAN	2 AND LONG TO SANDER	is a control of the c
mm/pulses	Pulses																									
1,0	500	•	•	•	•	•	•																			
0.1	5000							•	•	•	•	•	•													
0.04	12500													•	•	•	•	•	•							
0.02	25000																			•	•	•	•	•	•	
VDC)																									
10 up to 3	30 HTL	•		•		•		•		•		•		•		•		•		•		•		•		
4.75 uo to	5.5 TTL		•		•		•		•		•		•		•		•		•		•		•		•	
Range of	appl.*	1	1	2	2	3	3	1	1	2	2	3	3	1	1	2	2	3	3	1	1	2	2	3	3	

www.wachendorff-automation.com/lmsma25

Range of application of the measuring wheels U = 200 mm / 500 mm

	*1	*2	*3
Measuring wheel			B
Systems	LMSxxxKH	LMSxxxKG	LMSxxxNG
Range of appl.	Plastic, painted surfaces, paper, paste- board, wood, metal, textiles.	Plastic, painted surfaces, paper, paste- board, wood, metal, textiles.	Textiles.

Does your application require other resolutions or pulse counts, measuring wheels, cable lengths or other accessories? Contact us. We are happy to help you find the optimal solution.







Easily mountable - with pre-assembled angle ... the LMSMA3x length measuring system

If direct mounting is not possible at the plant, we have a solution for it. Varied mounting positions are possible with the highly variable orientable angle bracket and the 36 locking positions of the hand wheel.

Special spring for durable uniform spring force

Angle bracket with elongated holes for any

Angle bracket with elongated holes for any installation on the plant, pre-assembled at the pivot point of the measuring system

Hand wheel with catch positions for the adjustment of the contact pressure

Measuring wheels with different surfaces for ideal adaptation to the measuring surface

Locking pin to determine the resting position during setup or maintenance

Captive central screw for fast installation and setup



LMSMA32 length measuring system (measuring wheel U = 200 mm / with angle bracket)

()		>/:	MSMA	SA PARAMENTAL STATES	o 2ax	NO 32 NO	20 Sand	3270	22 ANG MASAN	SO S	2210	OS AND	2 AX	SON SON	2 Are	SOUND OF THE PROPERTY OF THE P	20 ACACACACACACACACACACACACACACACACACACAC	OSYN SON	So A	SO ASSO ASSO ASSO ASSO ASSO ASSO ASSO A	2 AND ASIASIASIASIASIASIASIASIASIASIASIASIASIA	NO STANDA	SON AND AND AND AND AND AND AND AND AND AN	NO STANSON	200 Sand	ist control of the co
mm/pulses	Pulses																									
1.0	200	•	•	•	•	•	•																			
0.1	2000							•	•	•	•	•	•													
0.04	5000													•	•	•	•	•	•							
0.008	25000																			•	•	•	•	•	•	
VDC																										
10 up to 3	30 HTL	•		•		•		•		•		•		•		•		•		•		•		•		
4.75 up to	5.5 TTL		•		•		•		•		•		•		•		•		•		•		•		•	
Range of	appl.*	1	1	2	2	3	3	1	1	2	2	3	3	1	1	2	2	3	3	1	1	2	2	3	3	

www.wachendorff-automation.com/lmsma32

LMSMA35 length measuring system (measuring wheel U = 500 mm / with angle bracket)

0		/3	NSWA T	35,00	San	NO STORY	No sak	NO STANDA	No sand	Store Contraction of the contrac	Day Control	ost of the state o	2 A CONTRACTOR	NO SO TO SO	2 Arts No.	OS NA STANKA	20 ACTOR	object of the state of the stat	2 de la	ost of the state o	2 ANG AG	No of the last of	No State	NO STANSING	No sake	et of the open
mm/pulses	Pulses																									
1.0	500	•	•	•	•	•	•																			
0.1	5000							•	•	•	•	•	•													
0.04	12500													•	•	•	•	•	•							
0.02	25000																			•	•	•	•	•	•	
VDC																										
10 up to 3	30 HTL	•		•		•		•		•		•		•		•		•		•		•		•		
4.75 up to	5.5 TTL		•		•		•		•		•		•		•		•		•		•		•		•	
Range of	appl.*	1	1	2	2	3	3	1	1	2	2	3	3	1	1	2	2	3	3	1	1	2	2	3	3	

www.wachendorff-automation.com/lmsma35

Range of application of the measuring wheels U = 200 mm / 500 mm

	*1	*2	*3
Measuring wheel			B
System	LMSxxxKH	LMSxxxKG	LMSxxxNG
Range of appl.	Cardboard, wood, soft plastics, textiles, leather, paper, wire, steel sections, greased metals and painted surfaces.	Cardboard, wood, soft plastics, textiles, rubber.	Cardboard, wood, plastics, coarse textiles, carpet, cable measurement, fleece, paper.

Does your application require other resolutions or pulse counts, measuring wheels, cable lengths or other accessories? Contact us. We are happy to help you find the optimal solution.

automation.com

www.wachendorff



The Wachendorff Group

- Delighted customers
- Corporate responsibility
- Attractive for good employees
- Outstanding quality
- Technology leader
- Environmental protection
- Profitable growth

We are a medium-sized owner-managed corporate group based in the beautiful Rheingau district, situated to the west of Wiesbaden.

Competent, personal, face-to-face advice and long-term collaboration with our business partners are the cornerstones of our continual growth. We are certified according to DIN ISO 9001:2015.

Wachendorff Automation GmbH & Co. KG

The development and manufacturing of rotary encoders, engine feedback devices and complete measuring systems for use in a wide range of serial production applications in mechanical and plant engineering. An extensive standard range featuring numerous options and efficient development of customised solutions.

Wachendorff Prozesstechnik GmbH & Co. KG

A reliable supplier since 1978 of robust, high quality industrial devices for visualizing, communicating and processing data in the areas of mechanical, plant and building automation.



Wachendorff Automation GmbH & Co. KG Industriestrasse 7 • D-65366 Geisenheim

Tel.: +49 (0) 67 22 / 99 65 - 25 Fax: +49 (0) 67 22 / 99 65 - 70 E-Mail: wdg@wachendorff.de www.wachendorff-automation.com



Your	dietrihi	ıtor.